

Examples for kinetic evaluations using mkin

Johannes Ranke

Eurofins Regulatory AG
Weidenweg 15, CH-4310 Rheinfelden, Switzerland

and

University of Bremen

November 6, 2013

Contents

1	Kinetic evaluations for parent compounds	1
1.1	Laboratory Data L1	1
1.2	Laboratory Data L2	7
1.3	Laboratory Data L3	16
1.4	Laboratory Data L4	22
2	Kinetic evaluations for parent and metabolites	26
2.1	Laboratory Data for example compound Z	26

Key words: Kinetics, FOCUS, nonlinear optimisation

1 Kinetic evaluations for parent compounds

These examples are also evaluated in a parallel vignette of the **kinfit** package (?). The datasets are from Appendix 3, of the FOCUS kinetics report (??).

1.1 Laboratory Data L1

The following code defines example dataset L1 from the FOCUS kinetics report, p. 284

```
R> library("mkin")
R> FOCUS_2006_L1 = data.frame(
+   t = rep(c(0, 1, 2, 3, 5, 7, 14, 21, 30), each = 2),
+   parent = c(88.3, 91.4, 85.6, 84.5, 78.9, 77.6,
+             72.0, 71.9, 50.3, 59.4, 47.0, 45.1,
+             27.7, 27.3, 10.0, 10.4, 2.9, 4.0))
R> FOCUS_2006_L1_mkin <- mkin_wide_to_long(FOCUS_2006_L1)
```

The next step is to set up the models used for the kinetic analysis. Note that the model definitions contain the names of the observed variables in the data. In this case, there is only one variable called **parent**.

```
R> SFO <- mkinmod(parent = list(type = "SFO"))
R> FOMC <- mkinmod(parent = list(type = "FOMC"))
R> DFOP <- mkinmod(parent = list(type = "DFOP"))
```

The three models cover the first assumption of simple first order (SFO), the case of declining rate constant over time (FOMC) and the case of two different phases of the kinetics (DFOP). For a more detailed discussion of the models, please see the FOCUS kinetics report.

The following two lines fit the model and produce the summary report of the model fit. This covers the numerical analysis given in the FOCUS report.

```
R> m.L1.SFO <- mkinfit(SFO, FOCUS_2006_L1_mkin, quiet=TRUE)
```

```
R> summary(m.L1.SFO)
```

```
mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:45 2013
Date of summary: Wed Nov 6 08:28:45 2013
```

Equations:

```
[1] d_parent = - k_parent_sink * parent
```

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100.0	state	100.000000
k_parent_sink	0.1	deparam	-2.302585

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	92.470	1.36800	89.570	95.370
k_parent_sink	-2.347	0.04057	-2.433	-2.261

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	92.47000	89.57000	95.3700
k_parent_sink	0.09561	0.08773	0.1042

Residual standard error: 2.948 on 16 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	3.424	2	7
parent	3.424	2	7

Estimated disappearance times:

	DT50	DT90
parent	7.249	24.08

Estimated formation fractions:

```

          ff
parent_sink  1


Parameter correlation:
      parent_0 k_parent_sink
parent_0      1.0000      0.6248
k_parent_sink  0.6248      1.0000

Data:
time variable observed predicted residual
  0   parent     88.3    92.471  -4.1710
  0   parent     91.4    92.471  -1.0710
  1   parent     85.6    84.039   1.5610
  1   parent     84.5    84.039   0.4610
  2   parent     78.9    76.376   2.5241
  2   parent     77.6    76.376   1.2241
  3   parent     72.0    69.412   2.5884
  3   parent     71.9    69.412   2.4884
  5   parent     50.3    57.330  -7.0301
  5   parent     59.4    57.330   2.0699
  7   parent     47.0    47.352  -0.3515
  7   parent     45.1    47.352  -2.2515
 14  parent     27.7    24.247   3.4527
 14  parent     27.3    24.247   3.0527
 21  parent     10.0    12.416  -2.4163
 21  parent     10.4    12.416  -2.0163
 30  parent      2.9    5.251  -2.3513
 30  parent      4.0    5.251  -1.2513

```


A plot of the fit is obtained with the plot function for mkinfit objects.

```
R> plot(m.L1.SF0)
```



The residual plot can be easily obtained by

```
R> mkinresplot(m.L1.SF0, ylab = "Observed", xlab = "Time")
```



For comparison, the FOMC model is fitted as well, and the χ^2 error level is checked.

```
R> m.L1.FOMC <- mkinfit(FOMC, FOCUS_2006_L1_mkin, quiet=TRUE)
```

```
R> summary(m.L1.FOMC)
```

```
mkin version:      0.9.23
R version:        3.0.1
Date of fit:     Wed Nov  6 08:28:45 2013
Date of summary: Wed Nov  6 08:28:45 2013
```

Equations:

```
[1] d_parent = - (alpha/beta) * ((time/beta) + 1)^{-1} * parent
```

Method used for solution of differential equation system:

analytical

Weighting: *none*

Starting values for optimised parameters:

	value	type	transformed
parent_0	100	state	100.000000
alpha	1	deparm	0.000000
beta	10	deparm	2.302585

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	92.47	NA	NA	NA
alpha	25.63	NA	NA	NA
beta	27.98	NA	NA	NA

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	9.247e+01	NA	NA
alpha	1.350e+11	NA	NA
beta	1.412e+12	NA	NA

Residual standard error: 3.045 on 15 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	3.619	3	6
parent	3.619	3	6

Estimated disappearance times:

	DT50	DT90
parent	7.249	24.08

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

Could not estimate covariance matrix; singular system:

Data:

time	variable	observed	predicted	residual
0	parent	88.3	92.471	-4.1711
0	parent	91.4	92.471	-1.0711
1	parent	85.6	84.038	1.5618
1	parent	84.5	84.038	0.4618
2	parent	78.9	76.377	2.5233
2	parent	77.6	76.377	1.2233
3	parent	72.0	69.412	2.5884
3	parent	71.9	69.412	2.4884
5	parent	50.3	57.331	-7.0306
5	parent	59.4	57.331	2.0694
7	parent	47.0	47.351	-0.3510
7	parent	45.1	47.351	-2.2510
14	parent	27.7	24.247	3.4526
14	parent	27.3	24.247	3.0526
21	parent	10.0	12.416	-2.4162
21	parent	10.4	12.416	-2.0162

```

30    parent      2.9      5.251   -2.3513
30    parent      4.0      5.251   -1.2513

```

Due to the higher number of parameters, and the lower number of degrees of freedom of the fit, the χ^2 error level is actually higher for the FOMC model (3.6%) than for the SFO model (3.4%). Additionally, the covariance matrix can not be obtained, indicating overparameterisation of the model.

The χ^2 error levels reported in Appendix 3 and Appendix 7 to the FOCUS kinetics report are rounded to integer percentages and partly deviate by one percentage point from the results calculated by `mkin`. The reason for this is not known. However, `mkin` gives the same χ^2 error levels as the `kinfit` package. Furthermore, the calculation routines of the `kinfit` package have been extensively compared to the results obtained by the KinGUI software, as documented in the `kinfit` package vignette. KinGUI is a widely used standard package in this field. Therefore, the reason for the difference was not investigated further.

1.2 Laboratory Data L2

The following code defines example dataset L2 from the FOCUS kinetics report, p. 287

```

R> FOCUS_2006_L2 = data.frame(
+   t = rep(c(0, 1, 3, 7, 14, 28), each = 2),
+   parent = c(96.1, 91.8, 41.4, 38.7,
+             19.3, 22.3, 4.6, 4.6,
+             2.6, 1.2, 0.3, 0.6))
R> FOCUS_2006_L2_mkin <- mkin_wide_to_long(FOCUS_2006_L2)

```

Again, the SFO model is fitted and a summary is obtained.

```

R> m.L2.SFO <- mkinfit(SFO, FOCUS_2006_L2_mkin, quiet=TRUE)
R> summary(m.L2.SFO)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:46 2013
Date of summary: Wed Nov 6 08:28:46 2013

```

Equations:

```
[1] d_parent = - k_parent_sink * parent
```

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100.000000	state	100.000000
k_parent_sink	0.100009	deparm	-2.302576

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	91.4700	3.8070	82.9800	99.9500
k_parent_sink	-0.4112	0.1074	-0.6505	-0.1719

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	91.4700	82.9800	99.9500
k_parent_sink	0.6629	0.5218	0.8421

Residual standard error: 5.51 on 10 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	14.38	2	4
parent	14.38	2	4

Estimated disappearance times:

	DT50	DT90
parent	1.046	3.474

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

	parent_0	k_parent_sink
parent_0	1.0000	0.4295
k_parent_sink	0.4295	1.0000



Data:

time	variable	observed	predicted	residual
0	parent	96.1	9.147e+01	4.6344
0	parent	91.8	9.147e+01	0.3344
1	parent	41.4	4.714e+01	-5.7395
1	parent	38.7	4.714e+01	-8.4395
3	parent	19.3	1.252e+01	6.7790
3	parent	22.3	1.252e+01	9.7790
7	parent	4.6	8.834e-01	3.7166
7	parent	4.6	8.834e-01	3.7166
14	parent	2.6	8.532e-03	2.5915
14	parent	1.2	8.532e-03	1.1915

```
28 parent      0.3 7.958e-07  0.3000
28 parent      0.6 7.958e-07  0.6000
```

The χ^2 error level of 14% suggests that the model does not fit very well. This is also obvious from the plots of the fit and the residuals.

```
R> par(mfrow = c(2, 1))
R> plot(m.L2.SF0)
R> mkinresplot(m.L2.SF0)
```



In the FOCUS kinetics report, it is stated that there is no apparent systematic error observed from the residual plot up to the measured DT90 (approximately at day 5), and

there is an underestimation beyond that point.

We may add that it is difficult to judge the random nature of the residuals just from the three samplings at days 0, 1 and 3. Also, it is not clear *a priori* why a consistent underestimation after the approximate DT90 should be irrelevant. However, this can be rationalised by the fact that the FOCUS fate models generally only implement SFO kinetics.

For comparison, the FOMC model is fitted as well, and the χ^2 error level is checked.

```
R> m.L2.FOMC <- mkinfit(FOMC, FOCUS_2006_L2_mkin, quiet = TRUE)
R> par(mfrow = c(2, 1))
R> plot(m.L2.FOMC)
R> mkinresplot(m.L2.FOMC)
R> summary(m.L2.FOMC, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:46 2013
Date of summary: Wed Nov 6 08:28:46 2013
```

Equations:

```
[1] d_parent = - (alpha/beta) * ((time/beta) + 1)^{-1} * parent
```

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100	state	100.000000
alpha	1	deparm	0.000000
beta	10	deparm	2.302585

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	93.7700	1.8560	89.5700	97.9700
alpha	0.3180	0.1867	-0.1044	0.7405
beta	0.2102	0.2943	-0.4556	0.8759

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	93.770	89.5700	97.970
alpha	1.374	0.9009	2.097
beta	1.234	0.6341	2.401

Residual standard error: 2.628 on 9 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	6.205	3	3
parent	6.205	3	3

Estimated disappearance times:



	DT50	DT90
parent	0.8092	5.356

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

	parent_0	alpha	beta
parent_0	1.00000	-0.09553	-0.1863
alpha	-0.09553	1.00000	0.9757
beta	-0.18628	0.97568	1.0000




The error level at which the χ^2 test passes is much lower in this case. Therefore, the FOMC model provides a better description of the data, as less experimental error has to

be assumed in order to explain the data.

Fitting the four parameter DFOP model further reduces the χ^2 error level.

```
R> m.L2.DFOP <- mkinfit(DFOP, FOCUS_2006_L2_mkin, quiet = TRUE)
R> plot(m.L2.DFOP)
```



Here, the default starting parameters for the DFOP model obviously do not lead to a reasonable solution. Therefore the fit is repeated with different starting parameters.

```
R> m.L2.DFOP <- mkinfit(DFOP, FOCUS_2006_L2_mkin,
+   parms.ini = c(k1 = 1, k2 = 0.01, g = 0.8),
+   quiet=TRUE)
R> plot(m.L2.DFOP)
R> summary(m.L2.DFOP, data = FALSE)

mkin version:      0.9.23
R version:         3.0.1
Date of fit:       Wed Nov  6 08:28:46 2013
Date of summary:   Wed Nov  6 08:28:47 2013
```

Equations:

```
[1] d_parent = - ((k1 * g * exp(-k1 * time) + k2 * (1 - g) * exp(-k2 * time)) / (g * exp(-k1 * time)))
```

Method used for solution of differential equation system:

analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	1e+02	state	100.0000000
k1	1e+00	deparm	0.0000000
k2	1e-02	deparm	-4.6051702
g	8e-01	deparm	0.9802581

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	93.9500		NA	NA
k1	4.9590		NA	NA
k2	-1.0880		NA	NA
g	-0.2821		NA	NA

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	93.9500	NA	NA
k1	142.4000	NA	NA
k2	0.3369	NA	NA
g	0.4016	NA	NA

Residual standard error: 1.732 on 8 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	2.53	4	2
parent	2.53	4	2

Estimated disappearance times:


	DT50	DT90
parent	NA	NA

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

Could not estimate covariance matrix; singular system:



Here, the DFOP model is clearly the best-fit model for dataset L2 based on the χ^2 error level criterion. However, the failure to calculate the covariance matrix indicates that the parameter estimates correlate excessively. Therefore, the FOMC model may be preferred for this dataset.

1.3 Laboratory Data L3

The following code defines example dataset L3 from the FOCUS kinetics report, p. 290.

```
R> FOCUS_2006_L3 = data.frame(
+   t = c(0, 3, 7, 14, 30, 60, 91, 120),
+   parent = c(97.8, 60, 51, 43, 35, 22, 15, 12))
R> FOCUS_2006_L3_mkin <- mkin_wide_to_long(FOCUS_2006_L3)
```

SFO model, summary and plot:

```
R> m.L3.SFO <- mkinfit(SFO, FOCUS_2006_L3_mkin, quiet = TRUE)
R> plot(m.L3.SFO)
R> summary(m.L3.SFO)

mkin version:      0.9.23
R version:          3.0.1
Date of fit:        Wed Nov  6 08:28:47 2013
```

Date of summary: Wed Nov 6 08:28:47 2013

Equations:

[1] $d_parent = -k_parent_sink * parent$

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100.000000	state	100.000000
k_parent_sink	0.1000005	deparm	-2.302581

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	74.870	8.4580	54.180	95.57
k_parent_sink	-3.678	0.3261	-4.476	-2.88

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	74.87000	54.18000	95.57000
k_parent_sink	0.02527	0.01138	0.05612

Residual standard error: 12.91 on 6 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	21.24	2	6
parent	21.24	2	6

Estimated disappearance times:

	DT50	DT90
parent	27.43	91.12

Estimated formation fractions:


	ff
parent_sink	1

Parameter correlation:

	parent_0	k_parent_sink
parent_0	1.0000	0.5484
k_parent_sink	0.5484	1.0000

Data:

time	variable	observed	predicted	residual
0	parent	97.8	74.873	22.92734
3	parent	60.0	69.407	-9.40654
7	parent	51.0	62.734	-11.73403
14	parent	43.0	52.563	-9.56336
30	parent	35.0	35.083	-0.08281
60	parent	22.0	16.439	5.56137
91	parent	15.0	7.510	7.48961
120	parent	12.0	3.609	8.39083



The χ^2 error level of 22% as well as the plot suggest that the model does not fit very well.

The FOMC model performs better:

```
R> m.L3.FOMC <- mkinfit(FOMC, FOCUS_2006_L3_mkin, quiet = TRUE)
R> plot(m.L3.FOMC)
R> summary(m.L3.FOMC, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:    Wed Nov  6 08:28:47 2013
Date of summary: Wed Nov  6 08:28:47 2013
```

Equations:

```
[1] d_parent = - (alpha/beta) * ((time/beta) + 1)^{-1} * parent
```

*Method used for solution of differential equation system:
analytical*

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100	state	100.000000
alpha	1	deparm	0.000000
beta	10	deparm	2.302585

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	96.9700	4.5500	85.2800	108.7000
alpha	-0.8619	0.1704	-1.3000	-0.4237
beta	0.6193	0.4744	-0.6003	1.8390

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	96.9700	85.2800	108.7000
alpha	0.4224	0.2725	0.6546
beta	1.8580	0.5487	6.2890

Residual standard error: 4.572 on 5 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	7.32	3	5
parent	7.32	3	5

Estimated disappearance times:


	DT50	DT90
parent	7.729	431.2

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

	parent_0	alpha	beta
parent_0	1.0000	-0.1512	-0.4271
alpha	-0.1512	1.0000	0.9110
beta	-0.4271	0.9110	1.0000



The error level at which the χ^2 test passes is 7% in this case.

Fitting the four parameter DFOP model further reduces the χ^2 error level considerably:

```
R> m.L3.DFOP <- mkinfit(DFOP, FOCUS_2006_L3_mkin, quiet = TRUE)
R> plot(m.L3.DFOP)
R> summary(m.L3.DFOP, data = FALSE)
```

```
mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:47 2013
Date of summary: Wed Nov 6 08:28:47 2013
```

Equations:

```
[1] d_parent = - ((k1 * g * exp(-k1 * time) + k2 * (1 - g) * exp(-k2 * time)) / (g * exp(-k1 * time)))
```

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	1e+02	state	100.000000
k1	1e-01	deparm	-2.302585
k2	1e-02	deparm	-4.605170

g *5e-01 deparm* *0.000000*

Fixed parameter values:

None

Optimised, transformed parameters:

	<i>Estimate</i>	<i>Std. Error</i>	<i>Lower</i>	<i>Upper</i>
<i>parent_0</i>	97.7500	1.43800	93.7500	101.70000
<i>k1</i>	-0.6612	0.13340	-1.0310	-0.29100
<i>k2</i>	-4.2860	0.05902	-4.4500	-4.12200
<i>g</i>	-0.1229	0.05121	-0.2651	0.01925

Backtransformed parameters:

	<i>Estimate</i>	<i>Lower</i>	<i>Upper</i>
<i>parent_0</i>	97.75000	93.75000	101.70000
<i>k1</i>	0.51620	0.35650	0.74750
<i>k2</i>	0.01376	0.01168	0.01621
<i>g</i>	0.45660	0.40730	0.50680

Residual standard error: 1.439 on 4 degrees of freedom

Chi2 error levels in percent:

	<i>err.min</i>	<i>n.optim</i>	<i>df</i>
All data	2.225	4	4
<i>parent</i>	2.225	4	4

Estimated disappearance times:


	<i>DT50</i>	<i>DT90</i>
<i>parent</i>	7.464	123

Estimated formation fractions:

	<i>ff</i>
<i>parent_sink</i>	1

Parameter correlation:

	<i>parent_0</i>	<i>k1</i>	<i>k2</i>	<i>g</i>
<i>parent_0</i>	1.00000	0.1640	0.01315	0.4253
<i>k1</i>	0.16399	1.0000	0.46477	-0.5526
<i>k2</i>	0.01315	0.4648	1.00000	-0.6631
<i>g</i>	0.42526	-0.5526	-0.66310	1.0000



Here, a look to the model plot, the confidence intervals of the parameters and the correlation matrix suggest that the parameter estimates are reliable, and the DFOP model can be used as the best-fit model based on the χ^2 error level criterion for laboratory data L3.

1.4 Laboratory Data L4

The following code defines example dataset L4 from the FOCUS kinetics report, p. 293

```
R> FOCUS_2006_L4 = data.frame(
+   t = c(0, 3, 7, 14, 30, 60, 91, 120),
+   parent = c(96.6, 96.3, 94.3, 88.8, 74.9, 59.9, 53.5, 49.0))
R> FOCUS_2006_L4_mkin <- mkin_wide_to_long(FOCUS_2006_L4)
```

SFO model, summary and plot:

```
R> m.L4.SFO <- mkinfit(SFO, FOCUS_2006_L4_mkin, quiet = TRUE)
R> plot(m.L4.SFO)
R> summary(m.L4.SFO, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:48 2013
Date of summary: Wed Nov 6 08:28:48 2013
```

Equations:

```
[1] d_parent = - k_parent_sink * parent
```

*Method used for solution of differential equation system:
analytical*

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100.000000	state	100.000000
k_parent_sink	0.1000004	deparm	-2.302581

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	96.44	1.94900	91.670	101.200
k_parent_sink	-5.03	0.07999	-5.225	-4.834

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	96.440000	91.670000	1.012e+02
k_parent_sink	0.006541	0.005378	7.955e-03

Residual standard error: 3.651 on 6 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	3.287	2	6
parent	3.287	2	6

Estimated disappearance times:


	DT50	DT90
parent	106	352

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

	parent_0	k_parent_sink
parent_0	1.0000	0.5865
k_parent_sink	0.5865	1.0000



The χ^2 error level of 3.3% as well as the plot suggest that the model fits very well.

The FOMC model for comparison

```
R> m.L4.FOMC <- mkinfit(FOMC, FOCUS_2006_L4_mkin, quiet = TRUE)
R> plot(m.L4.FOMC)
R> summary(m.L4.FOMC, data = FALSE)

mkin version:      0.9.23
R version:          3.0.1
Date of fit:       Wed Nov  6 08:28:48 2013
Date of summary:   Wed Nov  6 08:28:48 2013
```

Equations:

```
[1] d_parent = - (alpha/beta) * ((time/beta) + 1)^{-1} * parent
```

Method used for solution of differential equation system:
analytical

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
parent_0	100	state	100.000000
alpha	1	deparm	0.000000
beta	10	deparm	2.302585

Fixed parameter values:

None

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
parent_0	99.1400	1.6800	94.820	103.5000
alpha	-0.3506	0.3725	-1.308	0.6068
beta	4.1740	0.5635	2.725	5.6230

Backtransformed parameters:

	Estimate	Lower	Upper
parent_0	99.1400	94.8200	103.500
alpha	0.7042	0.2703	1.835
beta	64.9800	15.2600	276.600

Residual standard error: 2.315 on 5 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	2.029	3	5
parent	2.029	3	5

Estimated disappearance times:


	DT50	DT90
parent	108.9	1644

Estimated formation fractions:

	ff
parent_sink	1

Parameter correlation:

	parent_0	alpha	beta
parent_0	1.0000	-0.5365	-0.6083
alpha	-0.5365	1.0000	0.9913
beta	-0.6083	0.9913	1.0000



The error level at which the χ^2 test passes is slightly lower for the FOMC model. However, the difference appears negligible.

2 Kinetic evaluations for parent and metabolites

2.1 Laboratory Data for example compound Z

The following code defines the example dataset from Appendix 7 to the FOCUS kinetics report, p.350

```
R> LOD = 0.5
R> FOCUS_2006_Z = data.frame(
+   t = c(0, 0.04, 0.125, 0.29, 0.54, 1, 2, 3, 4, 7, 10, 14, 21,
+         42, 61, 96, 124),
+   Z0 = c(100, 81.7, 70.4, 51.1, 41.2, 6.6, 4.6, 3.9, 4.6, 4.3, 6.8,
+         2.9, 3.5, 5.3, 4.4, 1.2, 0.7),
+   Z1 = c(0, 18.3, 29.6, 46.3, 55.1, 65.7, 39.1, 36, 15.3, 5.6, 1.1,
+         1.6, 0.6, 0.5 * LOD, NA, NA, NA),
+   Z2 = c(0, NA, 0.5 * LOD, 2.6, 3.8, 15.3, 37.2, 31.7, 35.6, 14.5,
+         0.8, 2.1, 1.9, 0.5 * LOD, NA, NA, NA),
```

```

+   Z3 = c(0, NA, NA, NA, NA, 0.5 * LOD, 9.2, 13.1, 22.3, 28.4, 32.5,
+         25.2, 17.2, 4.8, 4.5, 2.8, 4.4))
R> FOCUS_2006_Z_mkin <- mkin_wide_to_long(FOCUS_2006_Z)

```

The next step is to set up the models used for the kinetic analysis. As the simultaneous fit of parent and the first metabolite is usually straightforward, Step 1 (SFO for parent only) is skipped here. We start with the model 2a, with formation and decline of metabolite Z1 and the pathway from parent directly to sink included (default in mkin).

```

R> Z.2a <- mkinmod(Z0 = list(type = "SFO", to = "Z1"),
+                     Z1 = list(type = "SFO"))
R> m.Z.2a <- mkinfit(Z.2a, FOCUS_2006_Z_mkin, quiet = TRUE)
R> plot(m.Z.2a)
R> summary(m.Z.2a, data = FALSE)

```

```

mkin version:      0.9.23
R version:        3.0.1
Date of fit:      Wed Nov  6 08:28:49 2013
Date of summary:  Wed Nov  6 08:28:49 2013

```

Equations:

```

[1] d_Z0 = - k_Z0_sink * Z0 - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - k_Z1_sink * Z1

```

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_0	100.0000000	state	100.000000
k_Z0_sink	0.1000009	deparm	-2.302577
k_Z0_Z1	0.1000005	deparm	-2.302580
k_Z1_sink	0.1000007	deparm	-2.302578

Fixed parameter values:

	value	type
Z1_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_0	97.0100	NA	NA	NA
k_Z0_sink	-36.2900	NA	NA	NA
k_Z0_Z1	0.8047	NA	NA	NA
k_Z1_sink	-0.7296	NA	NA	NA

Backtransformed parameters:

	<i>Estimate</i>	<i>Lower</i>	<i>Upper</i>
<i>Z0_0</i>	9.701e+01	NA	NA
<i>k_Z0_sink</i>	1.733e-16	NA	NA
<i>k_Z0_Z1</i>	2.236e+00	NA	NA
<i>k_Z1_sink</i>	4.821e-01	NA	NA

Residual standard error: 5.064 on 27 degrees of freedom

Chi2 error levels in percent:

	<i>err.min</i>	<i>n.optim</i>	<i>df</i>
All data	17.89	4	26
<i>Z0</i>	18.04	3	14
<i>Z1</i>	15.08	1	12

Estimated disappearance times:


	<i>DT50</i>	<i>DT90</i>
<i>Z0</i>	0.310	1.030
<i>Z1</i>	1.438	4.776

Estimated formation fractions:

	<i>ff</i>
<i>Z0_sink</i>	7.75e-17
<i>Z0_Z1</i>	1.00e+00
<i>Z1_sink</i>	1.00e+00

Parameter correlation:

Could not estimate covariance matrix; singular system:



As obvious from the summary, the kinetic rate constant from parent compound Z to sink is negligible. Accordingly, the exact magnitude of the fitted parameter $\log k_{Z_sink}$ is ill-defined and the covariance matrix is not returned. This suggests, in agreement with the analysis in the FOCUS kinetics report, to simplify the model by removing the pathway to sink.

A similar result can be obtained when formation fractions are used in the model formulation:

```
R> Z.2a.ff <- mkinmod(Z0 = list(type = "SFO", to = "Z1"),
+                         Z1 = list(type = "SFO"), use_of_ff = "max")
R> m.Z.2a.ff <- mkinfit(Z.2a.ff, FOCUS_2006_Z_mkin, quiet = TRUE)
R> plot(m.Z.2a.ff)
R> summary(m.Z.2a.ff, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:    Wed Nov  6 08:28:49 2013
Date of summary: Wed Nov  6 08:28:50 2013
```

Equations:

```
[1] d_Z0 = - k_Z0 * Z0
[2] d_Z1 = + f_Z0_to_Z1 * k_Z0 * Z0 - k_Z1 * Z1
```

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
<i>z0_0</i>	100.000000	state	100.000000
<i>k_z0</i>	0.1000001	deparm	-2.3025842
<i>f_z0_to_z1</i>	0.2000000	deparm	-0.9802581
<i>k_z1</i>	0.1000000	deparm	-2.3025848

Fixed parameter values:

	value	type
<i>z1_0</i>	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
<i>z0_0</i>	97.0100	NA	NA	NA
<i>k_z0</i>	0.8047	NA	NA	NA
<i>f_z0_to_z1</i>	21.5900	NA	NA	NA
<i>k_z1</i>	-0.7296	NA	NA	NA

Backtransformed parameters:

	Estimate	Lower	Upper
<i>z0_0</i>	97.0100	NA	NA
<i>k_z0</i>	2.2360	NA	NA
<i>f_z0_to_z1</i>	1.0000	NA	NA
<i>k_z1</i>	0.4821	NA	NA

Residual standard error: 5.064 on 27 degrees of freedom

Chi2 error levels in percent:


	err.min	n.optim	df
All data	17.89	4	26
<i>z0</i>	17.56	2	15
<i>z1</i>	15.59	2	11

Estimated disappearance times:

	DT50	DT90
<i>z0</i>	0.310	1.030
<i>z1</i>	1.438	4.776

Parameter correlation:

Could not estimate covariance matrix; singular system:



Here, the ilr transformed formation fraction fitted in the model takes a very large value, and the backtransformed formation fraction from parent Z to Z1 is practically unity. Again, the covariance matrix is not returned as the model is overparameterised.

The simplified model is obtained by setting the list component `sink` to `FALSE`. This model definition is not supported when formation fractions are used.

```
R> Z.3 <- mkinmod(Z0 = list(type = "SFO", to = "Z1", sink = FALSE),
+                     Z1 = list(type = "SFO"))
R> m.Z.3 <- mkinfit(Z.3, FOCUS_2006_Z_mkin, parms.ini = c(k_Z0_Z1 = 0.5),
+                      quiet = TRUE)
R> #m.Z.3 <- mkinfit(Z.3, FOCUS_2006_Z_mkin, solution_type = "deSolve")
R> plot(m.Z.3)
R> summary(m.Z.3, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:50 2013
Date of summary: Wed Nov 6 08:28:50 2013
```

Equations:

```
[1] d_Z0 = - 0 - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - k_Z1_sink * Z1
```

*Method used for solution of differential equation system:
eigen*

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
<i>z0_0</i>	100.0000000	state	100.0000000
<i>k_z0_z1</i>	0.5000000	deparm	-0.6931472
<i>k_z1_sink</i>	0.1000004	deparm	-2.3025810

Fixed parameter values:

	value	type
<i>z1_0</i>	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
<i>z0_0</i>	97.0100	2.68200	91.5200	102.5000
<i>k_z0_z1</i>	0.8047	0.06568	0.6702	0.9392
<i>k_z1_sink</i>	-0.7296	0.08854	-0.9109	-0.5482

Backtransformed parameters:

	Estimate	Lower	Upper
<i>z0_0</i>	97.0100	91.5200	102.500
<i>k_z0_z1</i>	2.2360	1.9550	2.558
<i>k_z1_sink</i>	0.4821	0.4022	0.578

Residual standard error: 4.973 on 28 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	17.61	3	27
<i>z0</i>	17.56	2	15
<i>z1</i>	15.08	1	12

Estimated disappearance times:

	DT50	DT90
<i>z0</i>	0.310	1.030
<i>z1</i>	1.438	4.776

Estimated formation fractions:

	ff
<i>z0_sink</i>	1
<i>z0_z1</i>	1
<i>z1_sink</i>	1


Parameter correlation:

	<i>z0_0</i>	<i>k_z0_z1</i>	<i>k_z1_sink</i>
<i>z0_0</i>	1.0000	0.10629	0.41038

```

k_Z0_Z1    0.1063 1.00000   0.04345
k_Z1_sink  0.4104 0.04345   1.00000

```



The first attempt to fit the model failed, as the default solution type chosen by mkinfit is based on eigenvalues, and the system defined by the starting parameters is identified as being singular to the solver. This is caused by the fact that the rate constants for both state variables are the same using the default starting parameters. Setting a different starting value for one of the parameters overcomes this. Alternatively, the **deSolve** based model solution can be chosen, at the cost of a bit more computing time.

```

R> Z.4a <- mkinmod(Z0 = list(type = "SF0", to = "Z1", sink = FALSE),
+                      Z1 = list(type = "SF0", to = "Z2"),
+                      Z2 = list(type = "SF0"))
R> m.Z.4a <- mkinfit(Z.4a, FOCUS_2006_Z_mkin, parms.ini = c(k_Z0_Z1 = 0.5),
+                        quiet = TRUE)
R> plot(m.Z.4a)
R> summary(m.Z.4a, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:     Wed Nov  6 08:28:51 2013
Date of summary: Wed Nov  6 08:28:51 2013

```

Equations:

```
[1] d_Z0 = - o - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - k_Z1_sink * Z1 - k_Z1_Z2 * Z1
[3] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2
```

*Method used for solution of differential equation system:
eigen*

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_0	100.000000	state	100.000000
k_Z0_Z1	0.5000000	deparm	-0.6931472
k_Z1_sink	0.1000008	deparm	-2.3025768
k_Z1_Z2	0.1000009	deparm	-2.3025763
k_Z2_sink	0.1000003	deparm	-2.3025823

Fixed parameter values:

	value	type
Z1_0	0	state
Z2_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_0	96.9600	2.44700	92.0100	101.9000
k_Z0_Z1	0.7970	0.05974	0.6762	0.9179
k_Z1_sink	-4.1040	4.84700	-13.9100	5.7000
k_Z1_Z2	-0.7667	0.14630	-1.0630	-0.4707
k_Z2_sink	-0.8410	0.22860	-1.3030	-0.3787

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_0	96.9600	9.201e+01	101.9000
k_Z0_Z1	2.2190	1.966e+00	2.5040
k_Z1_sink	0.0165	9.110e-07	298.9000
k_Z1_Z2	0.4645	3.455e-01	0.6245
k_Z2_sink	0.4313	2.716e-01	0.6848

Residual standard error: 4.54 on 39 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	19.31	5	37
Z0	17.47	2	15
Z1	15.71	2	11
Z2	19.54	1	11

Estimated disappearance times:

DT50 DT90

```

Z0 0.3124 1.038
Z1 1.4410 4.787
Z2 1.6072 5.339


```

Estimated formation fractions:

ff
Z0_sink 1.0000
Z0_Z1 1.0000
Z1_sink 0.0343
Z1_Z2 0.9657
Z2_sink 1.0000

Parameter correlation:

	Z0_0	k_Z0_Z1	k_Z1_sink	k_Z1_Z2	k_Z2_sink
Z0_0	1.0000	0.1064	0.3492	-0.1769	-0.1534
k_Z0_Z1	0.1064	1.0000	0.1479	-0.1501	-0.1226
k_Z1_sink	0.3492	0.1479	1.0000	-0.8745	-0.8656
k_Z1_Z2	-0.1769	-0.1501	-0.8745	1.0000	0.8190
k_Z2_sink	-0.1534	-0.1226	-0.8656	0.8190	1.0000



As suggested in the FOCUS report, the pathway to sink was removed for metabolite Z1 as well in the next step. While this step appears questionable on the basis of the above results, it is followed here for the purpose of comparison. Also, in the FOCUS report, it is assumed that there is additional empirical evidence that Z1 quickly and exclusively hydrolyses to Z2. Again, in order to avoid a singular system when using default starting

parameters, the starting parameter for the pathway without sink term has to be adapted.

```
R> Z.5 <- mkinmod(Z0 = list(type = "SFO", to = "Z1", sink = FALSE),
+                     Z1 = list(type = "SFO", to = "Z2", sink = FALSE),
+                     Z2 = list(type = "SFO"))
R> m.Z.5 <- mkinfit(Z.5, FOCUS_2006_Z_mkin,
+                      parms.ini = c(k_Z0_Z1 = 0.5, k_Z1_Z2 = 0.2), quiet = TRUE)
R> plot(m.Z.5)
R> summary(m.Z.5, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:52 2013
Date of summary: Wed Nov 6 08:28:52 2013
```

Equations:

```
[1] d_Z0 = - 0 - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - 0 - k_Z1_Z2 * Z1
[3] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2
```

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_0	100.0000000	state	100.0000000
k_Z0_Z1	0.5000000	deparm	-0.6931472
k_Z1_Z2	0.2000000	deparm	-1.6094379
k_Z2_sink	0.1000003	deparm	-2.3025820

Fixed parameter values:

	value	type
Z1_0	0	state
Z2_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_0	96.7700	2.26600	92.1900	101.3000
k_Z0_Z1	0.7948	0.05843	0.6767	0.9129
k_Z1_Z2	-0.7410	0.06821	-0.8789	-0.6032
k_Z2_sink	-0.8027	0.11090	-1.0270	-0.5785

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_0	96.7700	92.1900	101.3000
k_Z0_Z1	2.2140	1.9670	2.4920

<i>k_Z1_Z2</i>	0.4766	0.4152	0.5471
<i>k_Z2_sink</i>	0.4481	0.3581	0.5607

Residual standard error: 4.486 on 40 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	19.10	4	38
<i>Z0</i>	17.43	2	15
<i>Z1</i>	15.27	1	12
<i>Z2</i>	19.57	1	11

Estimated disappearance times:


	DT50	DT90
<i>Z0</i>	0.3131	1.040
<i>Z1</i>	1.4543	4.831
<i>Z2</i>	1.5468	5.138

Estimated formation fractions:

	ff
<i>Z0_sink</i>	1
<i>Z0_Z1</i>	1
<i>Z1_sink</i>	1
<i>Z1_Z2</i>	1
<i>Z2_sink</i>	1

Parameter correlation:

	<i>Z0_0</i>	<i>k_Z0_Z1</i>	<i>k_Z1_Z2</i>	<i>k_Z2_sink</i>
<i>Z0_0</i>	1.00000	0.05781	0.28747	0.31786
<i>k_Z0_Z1</i>	0.05781	1.00000	-0.04361	0.01212
<i>k_Z1_Z2</i>	0.28747	-0.04361	1.00000	0.24018
<i>k_Z2_sink</i>	0.31786	0.01212	0.24018	1.00000



Finally, metabolite Z3 is added to the model.

```
R> Z.FOCUS <- mkinmod(Z0 = list(type = "SFO", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO", to = "Z2", sink = FALSE),
+                         Z2 = list(type = "SFO", to = "Z3"),
+                         Z3 = list(type = "SFO"))
R> m.Z.FOCUS <- mkinfit(Z.FOCUS, FOCUS_2006_Z_mkin,
+                           parms.ini = c(k_Z0_Z1 = 0.5, k_Z1_Z2 = 0.2, k_Z2_Z3 = 0.3),
+                           quiet = TRUE)
R> plot(m.Z.FOCUS)
R> summary(m.Z.FOCUS, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:28:53 2013
Date of summary: Wed Nov 6 08:28:53 2013
```

Equations:

```
[1] d_Z0 = - 0 - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - 0 - k_Z1_Z2 * Z1
[3] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2 - k_Z2_Z3 * Z2
[4] d_Z3 = + k_Z2_Z3 * Z2 - k_Z3_sink * Z3
```

Method used for solution of differential equation system:

eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_0	100.0000000	state	100.0000000
k_Z0_Z1	0.5000000	deparm	-0.6931472
k_Z1_Z2	0.2000000	deparm	-1.6094379
k_Z2_Z3	0.3000000	deparm	-1.2039728
k_Z2_sink	0.1000001	deparm	-2.3025843
k_Z3_sink	0.1000009	deparm	-2.3025758

Fixed parameter values:

	value	type
Z1_0	0	state
Z2_0	0	state
Z3_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_0	96.8400	2.05900	92.7100	101.0000
k_Z0_Z1	0.7954	0.05332	0.6884	0.9025
k_Z1_Z2	-0.7375	0.06123	-0.8604	-0.6146
k_Z2_Z3	-1.5470	0.12250	-1.7930	-1.3010
k_Z2_sink	-1.4330	0.17160	-1.7770	-1.0880
k_Z3_sink	-2.8350	0.24360	-3.3240	-2.3470

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_0	96.84000	92.71000	101.0000
k_Z0_Z1	2.21500	1.99100	2.4660
k_Z1_Z2	0.47830	0.42300	0.5409
k_Z2_Z3	0.21290	0.16650	0.2723
k_Z2_sink	0.23870	0.16910	0.3368
k_Z3_sink	0.05869	0.03599	0.0957

Residual standard error: 4.1 on 51 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	19.23	6	48
Z0	17.45	2	15
Z1	15.24	1	12
Z2	20.32	2	10
Z3	11.89	1	11

Estimated disappearance times:

DT50 DT90

```

Z0  0.3129  1.039
Z1  1.4492  4.814
Z2  1.5348  5.099
Z3  11.8101 39.232


```

Estimated formation fractions:

ff
Z0_sink 1.0000
Z0_Z1 1.0000
Z1_sink 1.0000
Z1_Z2 1.0000
Z2_sink 0.5285
Z2_Z3 0.4715
Z3_sink 1.0000


Parameter correlation:

	Z0_0	k_Z0_Z1	k_Z1_Z2	k_Z2_Z3	k_Z2_sink	k_Z3_sink
Z0_0	1.00000	0.05387	0.2727	-0.07296	0.37006	-0.11348
k_Z0_Z1	0.05387	1.00000	-0.0521	-0.03581	0.02442	-0.02521
k_Z1_Z2	0.27275	-0.05210	1.0000	-0.12132	0.29384	-0.19144
k_Z2_Z3	-0.07296	-0.03581	-0.1213	1.00000	-0.18887	0.55155
k_Z2_sink	0.37006	0.02442	0.2938	-0.18887	1.00000	-0.64293
k_Z3_sink	-0.11348	-0.02521	-0.1914	0.55155	-0.64293	1.00000



This is the fit corresponding to the final result chosen in Appendix 7 of the FOCUS report. The residual plots can be obtained by

```
R> par(mfrow = c(2, 2))
R> mkinresplot(m.Z.FOCUS, "Z0", lpos = "bottomright")
R> mkinresplot(m.Z.FOCUS, "Z1", lpos = "bottomright")
R> mkinresplot(m.Z.FOCUS, "Z2", lpos = "bottomright")
R> mkinresplot(m.Z.FOCUS, "Z3", lpos = "bottomright")
```



As the FOCUS report states, there is a certain tailing of the time course of metabolite Z3. Also, the time course of the parent compound is not fitted very well using the SFO model, as residues at a certain low level remain.

Therefore, an additional model is offered here, using the single first-order reversible binding (SFORB) model for metabolite Z3. As expected, the χ^2 error level is lower for metabolite Z3 using this model and the graphical fit for Z3 is improved. However, the covariance matrix is not returned.

```
R> Z.mkin.1 <- mkinmod(Z0 = list(type = "SFO", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO", to = "Z2", sink = FALSE),
+                         Z2 = list(type = "SFO", to = "Z3"),
+                         Z3 = list(type = "SFORB"))
R> m.Z.mkin.1 <- mkinfit(Z.mkin.1, FOCUS_2006_Z_mkin,
+                           parms.ini = c(k_Z0_Z1 = 0.5, k_Z1_Z2 = 0.3),
+                           quiet = TRUE)
R> plot(m.Z.mkin.1)
R> summary(m.Z.mkin.1, data = FALSE)

mkin version: 0.9.23
R version: 3.0.1
Date of fit: Wed Nov 6 08:29:00 2013
Date of summary: Wed Nov 6 08:29:00 2013

Equations:
[1] d_Z0 = - 0 - k_Z0_Z1 * Z0
[2] d_Z1 = + k_Z0_Z1 * Z0 - 0 - k_Z1_Z2 * Z1
[3] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2 - k_Z2_Z3_free * Z2
[4] d_Z3_free = + k_Z2_Z3_free * Z2 - k_Z3_free_sink * Z3_free - k_Z3_free_bound * Z3_free
[5] d_Z3_bound = + k_Z3_free_bound * Z3_free - k_Z3_bound_free * Z3_bound

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:
      value   type transformed
Z0_0    100.0000000 state 100.0000000
k_Z0_Z1  0.5000000 deparm -0.6931472
k_Z1_Z2  0.3000000 deparm -1.2039728
k_Z2_sink 0.1000010 deparm -2.3025755
k_Z2_Z3_free 0.1000003 deparm -2.3025819
k_Z3_free_sink 0.1000008 deparm -2.3025767
k_Z3_free_bound 0.1000000 deparm -2.3025851
k_Z3_bound_free 0.0200000 deparm -3.9120230

Fixed parameter values:
      value   type
Z1_0      0 state
Z2_0      0 state
```

Z3_free_0 0 state
Z3_bound_0 0 state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
<i>Z0_0</i>	96.7400	NA	NA	NA
<i>k_Z0_Z1</i>	0.7947	NA	NA	NA
<i>k_Z1_Z2</i>	-0.7426	NA	NA	NA
<i>k_Z2_sink</i>	-1.4950	NA	NA	NA
<i>k_Z2_Z3_free</i>	-1.5040	NA	NA	NA
<i>k_Z3_free_sink</i>	-2.6540	NA	NA	NA
<i>k_Z3_free_bound</i>	-5.2440	NA	NA	NA
<i>k_Z3_bound_free</i>	-27.3300	NA	NA	NA

Backtransformed parameters:

	Estimate	Lower	Upper
<i>Z0_0</i>	9.674e+01	NA	NA
<i>k_Z0_Z1</i>	2.214e+00	NA	NA
<i>k_Z1_Z2</i>	4.759e-01	NA	NA
<i>k_Z2_sink</i>	2.243e-01	NA	NA
<i>k_Z2_Z3_free</i>	2.222e-01	NA	NA
<i>k_Z3_free_sink</i>	7.034e-02	NA	NA
<i>k_Z3_free_bound</i>	5.279e-03	NA	NA
<i>k_Z3_bound_free</i>	1.345e-12	NA	NA

Residual standard error: 4.107 on 49 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	19.230	8	46
<i>Z0</i>	17.429	2	15
<i>Z1</i>	15.275	1	12
<i>Z2</i>	20.279	2	10
<i>Z3</i>	8.222	3	9

Estimated disappearance times:

	DT50	DT90
<i>Z0</i>	0.3131	1.040
<i>Z1</i>	1.4566	4.839
<i>Z2</i>	1.5523	5.157
<i>Z3</i>	10.1978	45.329

Estimated formation fractions:

	ff
<i>Z0_sink</i>	1.0000
<i>Z0_Z1</i>	1.0000
<i>Z1_sink</i>	1.0000
<i>Z1_Z2</i>	1.0000
<i>Z2_sink</i>	0.5024


```
Z2_Z3_free    0.4976
Z3_free_sink 1.0000
```

Estimated Eigenvalues of SFORB model(s) :

Z3_b1	Z3_b2
7.562e-02	1.251e-12

Parameter correlation:

Could not estimate covariance matrix; singular system:



Therefore, a further stepwise model building is performed starting from the stage of parent and one metabolite, starting from the assumption that the model fit for the parent compound can be improved by using the SFORB model.

```
R> Z.mkin.2 <- mkinmod(Z0 = list(type = "SFORB", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO"))
R> m.Z.mkin.2 <- mkinfit(Z.mkin.2, FOCUS_2006_Z_mkin, quiet = TRUE)
R> plot(m.Z.mkin.2)
R> summary(m.Z.mkin.2, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:     Wed Nov  6 08:29:01 2013
Date of summary: Wed Nov  6 08:29:01 2013
```

Equations:

```
[1] d_Z0_free = - 0 - k_Z0_free_bound * Z0_free + k_Z0_bound_free * Z0_bound - k_Z0_free_bound * Z0_free_bound * Z0_free + k_Z0_bound_free * Z0_bound - k_Z0_bound_free * Z0_bound
```

```
[2] d_Z0_bound = + k_Z0_free_bound * Z0_free - k_Z0_bound_free * Z0_bound
```

```
[3] d_Z1 = + k_Z0_free_Z1 * Z0_free - k_Z1_sink * Z1
```

Method used for solution of differential equation system:

eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_free_0	100.0000000	state	100.000000
k_Z0_free_bound	0.1000000	deparm	-2.302585
k_Z0_bound_free	0.0200000	deparm	-3.912023
k_Z0_free_Z1	0.1000001	deparm	-2.302584
k_Z1_sink	0.1000010	deparm	-2.302575

Fixed parameter values:

	value	type
Z0_bound_0	0	state
Z1_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_free_0	97.2900	2.39500	92.3600	102.2000
k_Z0_free_bound	-2.0820	0.43220	-2.9710	-1.1940
k_Z0_bound_free	-4.7200	1.60500	-8.0190	-1.4220
k_Z0_free_Z1	0.8549	0.06430	0.7227	0.9871
k_Z1_sink	-0.7934	0.08506	-0.9682	-0.6185

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_free_0	97.290000	9.236e+01	102.2000
k_Z0_free_bound	0.124700	5.128e-02	0.3031
k_Z0_bound_free	0.008911	3.291e-04	0.2413
k_Z0_free_Z1	2.351000	2.060e+00	2.6830
k_Z1_sink	0.452300	3.798e-01	0.5387

Residual standard error: 4.438 on 26 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	15.63	5	25
Z0	14.74	4	13
Z1	14.31	1	12

Estimated disappearance times:

DT50 DT90

Z_0 0.302 1.190
 Z_1 1.532 5.091

Estimated formation fractions:


ff
 $Z_0_free_sink$ 1
 $Z_0_free_Z_1$ 1
 Z_1_sink 1

Estimated Eigenvalues of SFORB model(s) :

$Z_0_b_1$ $Z_0_b_2$
2.476314 0.008461

Parameter correlation:

	$Z_0_free_0$	$k_Z_0_free_bound$	$k_Z_0_bound_free$
$Z_0_free_0$	1.000000	0.006494	0.03324
$k_Z_0_free_bound$	0.006494	1.000000	0.54647
$k_Z_0_bound_free$	0.033238	0.546465	1.00000
$k_Z_0_free_Z_1$	0.111819	0.413926	0.15837
$k_Z_1_sink$	0.391553	-0.291911	-0.12597
	$k_Z_0_free_Z_1$	$k_Z_1_sink$	
$Z_0_free_0$	0.11182	0.39155	
$k_Z_0_free_bound$	0.41393	-0.29191	
$k_Z_0_bound_free$	0.15837	-0.12597	
$k_Z_0_free_Z_1$	1.00000	-0.04188	
$k_Z_1_sink$	-0.04188	1.00000	



When metabolite Z2 is added, the additional sink for Z1 is turned off again, for the same reasons as in the original analysis.

```
R> Z.mkin.3 <- mkinmod(Z0 = list(type = "SFORB", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO", to = "Z2"),
+                         Z2 = list(type = "SFO"))
R> m.Z.mkin.3 <- mkinfit(Z.mkin.3, FOCUS_2006_Z_mkin, quiet = TRUE)
R> plot(m.Z.mkin.3)
R> summary(m.Z.mkin.3, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:     Wed Nov  6 08:29:04 2013
Date of summary: Wed Nov  6 08:29:04 2013

Equations:
[1] d_Z0_free = - k_Z0_free_bound * Z0_free + k_Z0_bound_free * Z0_bound - k_Z0_free
[2] d_Z0_bound = + k_Z0_free_bound * Z0_free - k_Z0_bound_free * Z0_bound
[3] d_Z1 = + k_Z0_free_Z1 * Z0_free - k_Z1_sink * Z1 - k_Z1_Z2 * Z1
[4] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2

Method used for solution of differential equation system:
eigen
```

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
<i>Z0_free_0</i>	100.0000000	state	100.000000
<i>k_Z0_free_bound</i>	0.1000000	deparm	-2.302585
<i>k_Z0_bound_free</i>	0.0200000	deparm	-3.912023
<i>k_Z0_free_Z1</i>	0.1000009	deparm	-2.302576
<i>k_Z1_sink</i>	0.1000003	deparm	-2.302582
<i>k_Z1_Z2</i>	0.1000006	deparm	-2.302579
<i>k_Z2_sink</i>	0.1000004	deparm	-2.302581

Fixed parameter values:

	value	type
<i>Z0_bound_0</i>	0	state
<i>Z1_0</i>	0	state
<i>Z2_0</i>	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
<i>Z0_free_0</i>	97.4400	2.312e+00	9.275e+01	1.021e+02
<i>k_Z0_free_bound</i>	-2.1490	4.126e-01	-2.985e+00	-1.313e+00
<i>k_Z0_bound_free</i>	-4.8380	1.637e+00	-8.155e+00	-1.521e+00
<i>k_Z0_free_Z1</i>	0.8457	5.956e-02	7.250e-01	9.664e-01
<i>k_Z1_sink</i>	-17.6300	2.506e+06	-5.078e+06	5.078e+06
<i>k_Z1_Z2</i>	-0.7812	1.059e-01	-9.957e-01	-5.667e-01
<i>k_Z2_sink</i>	-0.8606	1.707e-01	-1.206e+00	-5.149e-01

Backtransformed parameters:

	Estimate	Lower	Upper
<i>Z0_free_0</i>	9.744e+01	9.275e+01	102.1000
<i>k_Z0_free_bound</i>	1.166e-01	5.055e-02	0.2691
<i>k_Z0_bound_free</i>	7.920e-03	2.872e-04	0.2184
<i>k_Z0_free_Z1</i>	2.330e+00	2.065e+00	2.6280
<i>k_Z1_sink</i>	2.200e-08	0.000e+00	Inf
<i>k_Z1_Z2</i>	4.579e-01	3.695e-01	0.5674
<i>k_Z2_sink</i>	4.229e-01	2.993e-01	0.5976

Residual standard error: 4.136 on 37 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	17.54	7	35
<i>Z0</i>	14.67	4	13
<i>Z1</i>	14.90	2	11
<i>Z2</i>	20.29	1	11

Estimated disappearance times:

	DT50	DT90
<i>Z0</i>	0.3043	1.185

Z1 1.5138 5.029
Z2 1.6391 5.445

Estimated formation fractions:

ff


<i>Z0_free_sink</i>	1.000e+00
<i>Z0_free_Z1</i>	1.000e+00
<i>Z1_sink</i>	4.805e-08
<i>Z1_Z2</i>	1.000e+00
<i>Z2_sink</i>	1.000e+00

Estimated Eigenvalues of SFORB model(s) :

<i>Z0_b1</i>	<i>Z0_b2</i>
2.446638	0.007542

Parameter correlation:

	<i>Z0_free_0</i>	<i>k_Z0_free_bound</i>	<i>k_Z0_bound_free</i>	
<i>Z0_free_0</i>	1.00000	0.01518	0.033545	
<i>k_Z0_free_bound</i>	0.01518	1.00000	0.545959	
<i>k_Z0_bound_free</i>	0.03354	0.54596	1.000000	
<i>k_Z0_free_Z1</i>	0.13432	0.40225	0.152314	
<i>k_Z1_sink</i>	0.41954	-0.12487	-0.072828	
<i>k_Z1_Z2</i>	-0.18395	-0.04229	0.003678	
<i>k_Z2_sink</i>	-0.16196	-0.03394	0.007076	
	<i>k_Z0_free_Z1</i>	<i>k_Z1_sink</i>	<i>k_Z1_Z2</i>	<i>k_Z2_sink</i>
<i>Z0_free_0</i>	0.1343	0.41954	-0.183953	-0.161962
<i>k_Z0_free_bound</i>	0.4022	-0.12487	-0.042291	-0.033937
<i>k_Z0_bound_free</i>	0.1523	-0.07283	0.003678	0.007076
<i>k_Z0_free_Z1</i>	1.0000	0.12526	-0.160310	-0.128025
<i>k_Z1_sink</i>	0.1253	1.00000	-0.783932	-0.778334
<i>k_Z1_Z2</i>	-0.1603	-0.78393	1.000000	0.716491
<i>k_Z2_sink</i>	-0.1280	-0.77833	0.716491	1.000000



This results in a much better representation of the behaviour of the parent compound Z0.

Finally, Z3 is added as well. This model appears overparameterised (no covariance matrix returned) if the sink for Z1 is left in the model.

```
R> Z.mkin.4 <- mkinmod(Z0 = list(type = "SFORB", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO", to = "Z2", sink = FALSE),
+                         Z2 = list(type = "SFO", to = "Z3"),
+                         Z3 = list(type = "SFO"))
R> m.Z.mkin.4 <- mkinfit(Z.mkin.4, FOCUS_2006_Z_mkin,
+                           parms.ini = c(k_Z1_Z2 = 0.05), quiet = TRUE)
R> plot(m.Z.mkin.4)
R> summary(m.Z.mkin.4, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:    Wed Nov  6 08:29:09 2013
Date of summary: Wed Nov  6 08:29:09 2013
```

Equations:

```
[1] d_Z0_free = - k_Z0_free_bound * Z0_free + k_Z0_bound_free * Z0_bound - k_Z0_free
[2] d_Z0_bound = + k_Z0_free_bound * Z0_free - k_Z0_bound_free * Z0_bound
[3] d_Z1 = + k_Z0_free_Z1 * Z0_free - k_Z1_Z2 * Z1
[4] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2 - k_Z2_Z3 * Z2
```

```
[5] d_Z3 = + k_Z2_Z3 * Z2 - k_Z3_sink * Z3
```

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_free_0	100.0000000	state	100.000000
k_Z1_Z2	0.0500000	deparm	-2.995732
k_Z0_free_bound	0.1000000	deparm	-2.302585
k_Z0_bound_free	0.0200000	deparm	-3.912023
k_Z0_free_Z1	0.1000002	deparm	-2.302583
k_Z2_sink	0.1000007	deparm	-2.302579
k_Z2_Z3	0.1000006	deparm	-2.302579
k_Z3_sink	0.1000003	deparm	-2.302582

Fixed parameter values:

	value	type
Z0_bound_0	0	state
Z1_0	0	state
Z2_0	0	state
Z3_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_free_0	97.5300	1.88700	93.7400	101.3000
k_Z1_Z2	-0.7769	0.05834	-0.8942	-0.6597
k_Z0_free_bound	-2.1360	0.36810	-2.8760	-1.3960
k_Z0_bound_free	-4.7650	1.41700	-7.6130	-1.9170
k_Z0_free_Z1	0.8470	0.05339	0.7398	0.9543
k_Z2_sink	-1.5610	0.18260	-1.9280	-1.1940
k_Z2_Z3	-1.5280	0.11350	-1.7560	-1.2990
k_Z3_sink	-2.7690	0.22460	-3.2200	-2.3180

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_free_0	97.53000	9.374e+01	101.3000
k_Z1_Z2	0.45980	4.089e-01	0.5170
k_Z0_free_bound	0.11810	5.636e-02	0.2475
k_Z0_bound_free	0.00852	4.938e-04	0.1470
k_Z0_free_Z1	2.33300	2.095e+00	2.5970
k_Z2_sink	0.20990	1.455e-01	0.3030
k_Z2_Z3	0.21700	1.728e-01	0.2727
k_Z3_sink	0.06272	3.994e-02	0.0985

Residual standard error: 3.737 on 49 degrees of freedom

Chi2 error levels in percent:

	<i>err.min</i>	<i>n.optim</i>	<i>df</i>
All data	17.50	8	46
Z0	14.69	4	13
Z1	14.39	1	12
Z2	21.05	2	10
Z3	11.76	1	11

Estimated disappearance times:

	<i>DT50</i>	<i>DT90</i>
Z0	0.304	1.186
Z1	1.507	5.008
Z2	1.623	5.393
Z3	11.051	36.712

Estimated formation fractions:


	<i>ff</i>
Z0_free_sink	1.0000
Z0_free_Z1	1.0000
Z1_sink	1.0000
Z1_Z2	1.0000
Z2_sink	0.4917
Z2_Z3	0.5083
Z3_sink	1.0000

Estimated Eigenvalues of SFORB model(s) :

<i>Z0_b1</i>	<i>Z0_b2</i>
2.451259	0.008108

Parameter correlation:

	<i>Z0_free_0</i>	<i>k_Z1_Z2</i>	<i>k_Z0_free_bound</i>	<i>k_Z0_bound_free</i>
<i>Z0_free_0</i>	1.00000	0.24238	0.07823	0.06921
<i>k_Z1_Z2</i>		0.24238	1.00000	-0.08934
<i>k_Z0_free_bound</i>		0.07823	-0.22742	1.00000
<i>k_Z0_bound_free</i>		0.06921	-0.08934	0.53976
<i>k_Z0_free_Z1</i>		0.08883	-0.10841	0.42766
<i>k_Z2_sink</i>		0.32993	0.34052	-0.26331
<i>k_Z2_Z3</i>		-0.07494	-0.14885	0.06698
<i>k_Z3_sink</i>		-0.10456	-0.22486	0.13845
	<i>k_Z0_free_Z1</i>	<i>k_Z2_sink</i>	<i>k_Z2_Z3</i>	<i>k_Z3_sink</i>
<i>Z0_free_0</i>	0.08883	0.3299	-0.07494	-0.10456
<i>k_Z1_Z2</i>		-0.10841	0.3405	-0.14885
<i>k_Z0_free_bound</i>		0.42766	-0.2633	0.06698
<i>k_Z0_bound_free</i>		0.16281	-0.1274	0.06082
<i>k_Z0_free_Z1</i>		1.00000	-0.0531	-0.01281
<i>k_Z2_sink</i>		-0.05310	1.0000	-0.25473
<i>k_Z2_Z3</i>		-0.01281	-0.2547	1.00000
<i>k_Z3_sink</i>		0.01858	-0.6832	0.56390



The error level of the fit, but especially of metabolite Z3, can be improved if the SFORB model is chosen for this metabolite, as this model is capable of representing the tailing of the metabolite decline phase.

Using the SFORB additionally for Z1 or Z2 did not further improve the result.

```
R> Z.mkin.5 <- mkinmod(Z0 = list(type = "SFORB", to = "Z1", sink = FALSE),
+                         Z1 = list(type = "SFO", to = "Z2", sink = FALSE),
+                         Z2 = list(type = "SFO", to = "Z3"),
+                         Z3 = list(type = "SFORB"))
R> m.Z.mkin.5 <- mkinfit(Z.mkin.5, FOCUS_2006_Z_mkin,
+                           parms.ini = c(k_Z1_Z2 = 0.2), quiet = TRUE)
R> plot(m.Z.mkin.5)
R> summary(m.Z.mkin.5, data = FALSE)

mkin version:      0.9.23
R version:        3.0.1
Date of fit:    Wed Nov  6 08:29:26 2013
Date of summary: Wed Nov  6 08:29:26 2013

Equations:
[1] d_Z0_free = - 0 - k_Z0_free_bound * Z0_free + k_Z0_bound_free * Z0_bound - k_Z0_free
[2] d_Z0_bound = + k_Z0_free_bound * Z0_free - k_Z0_bound_free * Z0_bound
[3] d_Z1 = + k_Z0_free_Z1 * Z0_free - 0 - k_Z1_Z2 * Z1
```

```
[4] d_Z2 = + k_Z1_Z2 * Z1 - k_Z2_sink * Z2 - k_Z2_Z3_free * Z2
[5] d_Z3_free = + k_Z2_Z3_free * Z2 - k_Z3_free_sink * Z3_free - k_Z3_free_bound * Z3_free
[6] d_Z3_bound = + k_Z3_free_bound * Z3_free - k_Z3_bound_free * Z3_bound
```

Method used for solution of differential equation system:
eigen

Weighting: none

Starting values for optimised parameters:

	value	type	transformed
Z0_free_0	100.000000	state	100.000000
k_Z1_Z2	0.2000000	deparm	-1.609438
k_Z0_free_bound	0.1000000	deparm	-2.302585
k_Z0_bound_free	0.0200000	deparm	-3.912023
k_Z0_free_Z1	0.1000002	deparm	-2.302583
k_Z2_sink	0.1000008	deparm	-2.302577
k_Z2_Z3_free	0.1000000	deparm	-2.302585
k_Z3_free_sink	0.1000006	deparm	-2.302579
k_Z3_free_bound	0.1000000	deparm	-2.302585
k_Z3_bound_free	0.0200000	deparm	-3.912023

Fixed parameter values:

	value	type
Z0_bound_0	0	state
Z1_0	0	state
Z2_0	0	state
Z3_free_0	0	state
Z3_bound_0	0	state

Optimised, transformed parameters:

	Estimate	Std. Error	Lower	Upper
Z0_free_0	97.4200	1.88200	93.6400	101.2000
k_Z1_Z2	-0.7823	0.05861	-0.9002	-0.6644
k_Z0_free_bound	-2.1400	0.36300	-2.8700	-1.4100
k_Z0_bound_free	-4.8390	1.41700	-7.6900	-1.9890
k_Z0_free_Z1	0.8464	0.05312	0.7395	0.9533
k_Z2_sink	-1.6340	0.22360	-2.0840	-1.1840
k_Z2_Z3_free	-1.4860	0.17810	-1.8440	-1.1270
k_Z3_free_sink	-2.5930	0.37420	-3.3460	-1.8410
k_Z3_free_bound	-5.2610	1.00200	-7.2760	-3.2460
k_Z3_bound_free	-17.0500	20.03000	-57.3500	23.2500

Backtransformed parameters:

	Estimate	Lower	Upper
Z0_free_0	9.742e+01	9.364e+01	1.012e+02
k_Z1_Z2	4.573e-01	4.065e-01	5.146e-01
k_Z0_free_bound	1.177e-01	5.668e-02	2.443e-01
k_Z0_bound_free	7.912e-03	4.575e-04	1.368e-01

<i>k_Z0_free_Z1</i>	2.331e+00	2.095e+00	2.594e+00
<i>k_Z2_sink</i>	1.952e-01	1.245e-01	3.060e-01
<i>k_Z2_Z3_free</i>	2.264e-01	1.582e-01	3.239e-01
<i>k_Z3_free_sink</i>	7.477e-02	3.522e-02	1.587e-01
<i>k_Z3_free_bound</i>	5.191e-03	6.919e-04	3.894e-02
<i>k_Z3_bound_free</i>	3.942e-08	1.243e-25	1.251e+10

Residual standard error: 3.73 on 47 degrees of freedom

Chi2 error levels in percent:

	err.min	n.optim	df
All data	17.434	10	44
Z0	14.669	4	13
Z1	14.404	1	12
Z2	21.054	2	10
Z3	8.095	3	9

Estimated disappearance times:

	DT50	DT90
Z0	0.3042	1.186
Z1	1.5156	5.035
Z2	1.6444	5.462
Z3	9.5687	41.058

Estimated formation fractions:

	ff
Z0_free_sink	1.000
Z0_free_Z1	1.000
Z1_sink	1.000
Z1_Z2	1.000
Z2_sink	0.463
Z2_Z3_free	0.537
Z3_free_sink	1.000


Estimated Eigenvalues of SFORB model(s) :

Z0_b1	Z0_b2	Z3_b1	Z3_b2
2.449e+00	7.531e-03	7.996e-02	3.686e-08

Parameter correlation:


	Z0_free_0	k_Z1_Z2	k_Z0_free_bound	k_Z0_bound_free
Z0_free_0	1.000000	0.246104	0.06614	0.05361
k_Z1_Z2	0.246104	1.000000	-0.24410	-0.11439
k_Z0_free_bound	0.066139	-0.244103	1.00000	0.52970
k_Z0_bound_free	0.053612	-0.114386	0.52970	1.00000
k_Z0_free_Z1	0.083075	-0.113942	0.42018	0.14740
k_Z2_sink	0.335105	0.358733	-0.15876	0.02971
k_Z2_Z3_free	-0.065530	-0.086307	-0.08455	-0.13972
k_Z3_free_sink	-0.095118	-0.227130	0.22917	0.27312
k_Z3_bound_free	-0.057690	0.009601	-0.38337	-0.58579

<i>k_Z3_bound_free</i>	-0.002904	0.048227	-0.05110	0.17308
<i>k_Z0_free_Z1</i>	0.083075	0.33510	-0.06553	-0.09512
<i>k_Z1_Z2</i>	-0.113942	0.35873	-0.08631	-0.22713
<i>k_Z0_free_bound</i>	0.420182	-0.15876	-0.08455	0.22917
<i>k_Z0_bound_free</i>	0.147397	0.02971	-0.13972	0.27312
<i>k_Z0_free_Z1</i>	1.000000	-0.01045	-0.07643	0.06862
<i>k_Z2_sink</i>	-0.010446	1.00000	0.08789	-0.68327
<i>k_Z2_Z3_free</i>	-0.076428	0.08789	1.00000	-0.07674
<i>k_Z3_free_sink</i>	0.068615	-0.68327	-0.07674	1.00000
<i>k_Z3_free_bound</i>	-0.175464	0.17434	0.53068	-0.27450
<i>k_Z3_bound_free</i>	0.007372	-0.27929	-0.76653	0.50567
		<i>k_Z3_free_bound</i>	<i>k_Z3_bound_free</i>	
<i>Z0_free_0</i>	-0.057690		-0.002904	
<i>k_Z1_Z2</i>	0.009601		0.048227	
<i>k_Z0_free_bound</i>	-0.383372		-0.051097	
<i>k_Z0_bound_free</i>	-0.585788		0.173081	
<i>k_Z0_free_Z1</i>	-0.175464		0.007372	
<i>k_Z2_sink</i>	0.174338		-0.279286	
<i>k_Z2_Z3_free</i>	0.530682		-0.766526	
<i>k_Z3_free_sink</i>	-0.274495		0.505672	
<i>k_Z3_free_bound</i>	1.000000		-0.545333	
<i>k_Z3_bound_free</i>	-0.545333		1.000000	



Looking at the confidence intervals of the SFORB model parameters of Z3, it is clear that nothing can be said about the degradation rate of Z3 towards the end of the experiment. However, this appears to be a feature of the data.

```
R> par(mfrow = c(2, 2))
R> mkinresplot(m.Z.mkin.5, "Z0", lpos = "bottomright")
R> mkinresplot(m.Z.mkin.5, "Z1", lpos = "bottomright")
R> mkinresplot(m.Z.mkin.5, "Z2", lpos = "bottomright")
R> mkinresplot(m.Z.mkin.5, "Z3", lpos = "bottomright")
```



As expected, the residual plots are much more random than in the case of the all SFO model for which they were shown above. In conclusion, the model `Z.mkin.5` is proposed as the best-fit model for the dataset from Appendix 7 of the FOCUS report.